

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

# 1. Identification

Product Name:	Alex Plus Acrylic Latex Caulk Plus Silicone - All Colors	Revision Date:	4/23/2020
Product UPC Number:	070798742376, 070798742390, 070798742451, 070798742475, 070798742253, 070798742437, 070798742338, 070798742772	Supercedes Date:	10/29/2018
Imported by	DAP Canada 475 Finchdene Square Unit 5 Scarborough, Ontario M1X 1B7 888-327-8477 (non - emergency matters)	Product Use/Class: SDS No: Preparer:	Caulking Compound 1700665 Regulatory and Environmental Affairs
	SDS Coordinator: MSDS@dap.com Emergency Telephone: 1-800-535-5053, 1-352-323-3500		

# 2. Hazards Identification

### **GHS Classification**

Not a hazardous substance or mixture.

#### Symbol(s) of Product

None

#### Signal Word

Not a hazardous substance or mixture.

#### **Possible Hazards**

16% of the mixture consists of ingredients of unknown acute toxicity

# 3. Composition/Information on Ingredients

<u>Chemical Name</u> Lubricating petroleum oil <u>CAS-No.</u> 72623-86-0 Wt. % GHS Symbols 5-10 GHS07 GHS Statements H332 The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### 4. First-aid Measures

**FIRST AID - INHALATION:** Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

### 5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

## 6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

### 7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling.

**STORAGE:** Avoid excessive heat and freezing. Do not store at temperatures above 120 degrees F. Store away from caustics and oxidizers.

### 8. Exposure Controls/Personal Protection

Ingredients with Occupational Expos	ure Limits			
Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING
Lubricating petroleum oil	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

### **Personal Protection**

**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required.



SKIN PROTECTION: Rubber gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



**HYGIENIC PRACTICES:** Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

## 9. Physical and Chemical Properties

Appearance: Odor:	Colored Very Slight Ammonia
Density, g/cm3:	1.57 - 1.58
Freeze Point, °C:	Not Established
Solubility in Water:	No Information
Decomposition Temperature, °C:	Not Established
Boiling Range, °C:	100 - 100
Minimum Flash Point, °C:	100
Evaporation Rate:	Slower Than n-Butyl Acetate
Vapor Density:	Heavier Than Air
Combustible Dust:	Does not support combustion

Physical State: Odor Threshold: pH: Viscosity (mPa.s): Partition Coeff., n-octanol/water: Explosive Limits, %: Auto-Ignition Temperature, °C Vapor Pressure, mmHg: Flash Method: Flammability, NFPA: Paste Not Established Between 7.0 and 12.0 Not Established Not Established N.E. - N.E. Not Established Not Established Seta Closed Cup Non-Flammable

(See "Other information" Section for abbreviation legend) (If product is an aerosol, the flash point stated above is that of the propellant.)

# 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

### 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** Under normal use conditions, this product is not expected to cause adverse health effects. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury.

#### CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause mild irritation of eyes and skin.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Inhalation

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	Chemical Name	<u>Oral LD50</u>	Dermal LD50	Vapor LC50
72623-86-0	Lubricating petroleum oil	>5000 mg/kg Rat	>2000 mg/kg Rabbit	N.I.

N.I. = No Information

## 12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

## 13. Disposal Information

**DISPOSAL INFORMATION:** This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

# 14. Transport Information

DOT UN/NA Number:	N.A.
DOT Proper Shipping Name: DOT Technical Name:	Not Regulated N.A.
DOT Hazard Class:	N.A.
Hazard SubClass:	N.A.
Packing Group:	N.A.

### 15. Regulatory Information

### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt. This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

# 16. Other Information

Revision Date:		4/23/2020	Supersedes Date:	10/29/2018
Reason for revision:		Revision Description Changed Product Composition Changed Substance and/or Product Properties Cha 01 - Product Information 05 - Flammability Information 09 - Physical & Chemical Information 16 - Other Information Revision Statement(s) Changed	nged in Section(s):	
Datasheet produced by: HMIS Ratings:		Regulatory Department		
Health:	Flammability:	Reactivity:	Personal Prote	ection:
1	0	0	Х	
		VOC Less Water	Less Exempt Solve	<b>nt, g/L:</b> 15.0

VOC Material, g/L: 11

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 0.03

VOC Actual, Wt/Wt%: 0.7

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H332 Harmful if inhaled. Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.